

Amendments to the Drawings

The attached sheets of drawings include changes to FIGS. 1-6. The following sheets, which includes FIG. 1-11, replaces the original sheets but do not add new matter. The numbering system on the original drawing sheets used a and b wherein the replacement sheets do not.

Attachment:

Replacement Sheet. FIG 1 for old FIG. 1 top illustration
Replacement Sheet. FIG 2 for old FIG. 1 bottom illustration
Replacement Sheet. FIG 3 for old FIG. 2a
Replacement Sheet. FIG 4 for old FIG. 2b
Replacement Sheet. FIG 5 for old FIG. 3a
Replacement Sheet. FIG 6 for old FIG. 3b
Replacement Sheet. FIG 7 for old FIG. 4a
Replacement Sheet. FIG 8 for old FIG. 4b
Replacement Sheet. FIG 9 for old FIG. 5a
Replacement Sheet. FIG 10 for old FIG. 5b
Replacement Sheet. FIG 11 for old FIG. 6


Appl. No. 10/796,538
Amendment. Dated May 26, 2006
Reply to Office Action of Jan 18, 2006



Remarks/Arguments

In light of the above noted amendments and remarks, this application is believed in condition for allowance and notice thereof is respectfully solicited. The Examiner is urged to contact applicant at (503) 622-3051 if there are any question.

Respectfully submitted,


Brian E. Hicks


Brian E Hicks
65766 E Sandy River Lane
Rhododendron Oregon 97049
(503) 622-3051

Certificate of Mailing

I hereby certify that this correspondence is being deposited as first class mail with the United States Postal Service in an envelope addressed to :

Mail Stop – Non Fee Amendments
Honorable Commissioner For Patents
PO Box 1450
Alexandria, VA 22313-1450

On this 26 day of MAY, 2006


Brian E Hicks

24
17



ATTACHED
MARKED UP COPY

April 10, 2006

MOUNTAINEERS COT

Background of the Invention

This invention relates to a sleeping cot, lightweight enough to be used by backpackers and mountaineers in lieu of the more commonly used therma-rest (inflatable pad) or the ridge rest (foam pad).

The mountaineers' cot will be a great addition to anyone's backcountry experience. With the relative little difference in weight to be carried, the backpacker could greatly increase his/her comfort regardless of ground conditions. By using tools already being used for other purposes' the user is reducing overall weight while greatly increasing comfort. The tools already in use are as follows: Telescoping ski poles, ice ax, sleeping pad, sleeping pad camp chair and internal frame backpack. The cot user will exchange the sleeping pad and chair for the cot fabric and six cot legs. By adapting the internal frame backpacking stays into the side-rails of the cot and using the trekking poles and ice ax as the end and center stays of the cot the user will have the ultimate in efficiency and comfort in the backcountry environment.

Currently in the sports of backpacking and mountaineering, the only lightweight sleeping pads are the therma-rest and the ridge rest. These sleeping pads, although relatively comfortable, have some significant disadvantages. For example: a therma-rest, while providing comfort and insulation, can fail if the barrier is breached causing an air leak and leaving the user in the position of sleeping on cold, icy, rocky, uncomfortable ground. The ridge rest being the lighter of the two is less comfortable and provides less insulation.

Formatted: Section start:
Continuous, From text: 0.8"
Formatted: Suppress line numbers
Deleted: March 2, 2004
Deleted: ¶
TITLE: Backpackers/mountaineers
cot.¶
BACKGROUND:
Formatted: Indent: First line: 0.5"

Deleted: SPECIFICATION:¶
Discussion of prior art:

Formatted: Indent: First line: 0.5"

Formatted: Position: Horizontal:
Center, Relative to: Margin

5 Prior art has discussed the use of a backpack cot, i.e. U.S. Patent #5590825, where the cot is incorporated into the external frame backpack. The disadvantages of this idea are that you are basically doubling the weight of your backpack. In addition, you are removing the storage capability of your pack for camping. You would have to displace the entire contents of your pack in order to deploy your cot. Furthermore, the external frame required for this patent

10 has greatly decreased in popularity over the last two decades for many reasons and current users of the external frame pack are not the target markets of this invention.

Summary of the Invention

The Mountaineers Cot will provide a lightweight, comfortable and firm flat sleeping surface regardless of the ground conditions. The cot incorporates tools already in use by the backpacker and mountaineer and therefore will have little effect on increasing the weight to be carried. Currently, many avid backpackers and mountaineers employ the use of telescoping ski poles or trekking poles, an ice ax if the terrain demands it and an internal frame pack. By incorporating all option levels of the Mountaineers cot, you would be carrying the cot cloth and six 6 inch legs. The trekking poles become the end stays of your cot. The ice ax is your center stay and the side rails come from the main stays of your internal frame pack. In addition, several different brands of internal frame packs use a relatively similar main stay system, a conversion from existing mainstay design to a mainstay that can act as the siderails of the cot can be manufactured to retrofit an individuals current pack allowing the owner to keep his/her original pack. The conversion will match up the metal stay ends of the existing pack requirements with telescoping siderails of the cot. The retrofit will then be made with varying sizes. The adjustable side rails and conversion could thus replace the existing mainstays. This full use of existing tools is called option 1.

Deleted: Objects and advantages:

Deleted: Backpacker/mountaineers cot

Formatted: Indent: First line: 0"

Deleted: /

Deleted: Hicks

Deleted: individual

Formatted: Position: Horizontal: Center, Relative to: Margin

5 When option 1 is not what the owner is interested in because he/she is happy with their current pack or the owner cannot afford the new pack, an individual can use option 2. Option 2 requires the user to carry the side rails in addition to the cloth and the six 6 inch legs. The increase in weight would be relative to a backpacker adding a sleeping pad chair to his/her pack. Special note: the sleeping pad chair is a popular option for backpacker that uses four

Deleted: s

10 independent poles stretched over by nylon with pockets on each end to stuff the foam sleeping pad or inflatable sleeping pad. Then the user uses straps to cinch the chair into a sitting position. Option 2 would only require the use of the ski poles and the ice ax. I will also note at this time that the mountaineers' cot will incorporate the use of four independent side rails and adjustable side straps so the user can use the cot as a camp chair similar to the sleeping pad

Deleted: backpacker/mountaineers

15 chair. Option 3 is simply the backpacker option. When using option 3, the only dual use incorporated is the use of the ski poles as the end stays. A standard center stay (ice ax extender) is used in lieu of the ice ax. Of course, the user could also elect to use the option 4

Deleted: The ice ax connections to the cot center legs will require a receiver for the point of the ice ax and then a receiver for the shaft of the ice ax on the other end in order to accommodate different size ice axes. The end receiver legs will be constructed as a trekking pole point receiver leg and trekking pole handle receiver leg

Deleted: four

20 backpack, without the ice ax and still be lightweight. The center stay will be the ice ax extender used to extend the length of shorter ice axes in order for the ice ax to fit to the cot as a center stay. The ice ax extender will come in a length that is fitted to the size of the center cot main stay but can be cut down by the user if he/she decides to use the ice ax center stay option.

25 Option 4 is simply an ultra light cot. It is not as light as a sleeping pad, but a perfect option for the packer looking for comfort. Option 4 could have a secondary target market in the hunter who is looking for the ultra light comfort, but with no need for the other options.

Formatted: Position: Horizontal; Center, Relative to: Margin

5

In addition, various cot cloths should be included in the options: a lighter weight mesh for warmer environments, an insulated cot for cold weather and a standard nylon single layer cloth for normal conditions.

5

10

15

20

25

Brief Description of Drawings

- FIG. 1 is an overhead view of the cot and its parts assembled for use.
- FIG. 2 is a side view of the cot and its parts assembled for use.
- FIG. 3 is a side view of a pole tip leg with a side-rail inserted in position.
- FIG. 4 is a front view of a pole tip leg with a pole tip inserted in position.
- FIG. 5 is a side view of a pole handle leg with side-rail inserted in position.
- FIG. 6 is a front view of a pole handle leg with a pole handle inserted in position.
- FIG. 7 is a side view of an ax point leg with side-rails inserted in position.
- FIG. 8 is a front view of an ax point leg with the point on the ax inserted in position.
- FIG. 9 is a side view of an ax head leg with the shaft of the ice ax inserted in position.
- FIG. 10 is the front view of an ax head leg with the shaft of the ice ax inserted in position.
- FIG. 11 is an overhead view of the ice ax extender.

Detailed Description of the Drawings

Figure 1 is an overall look at the cot when it is assembled and the position of all of the related material necessary to have the cot assembled. Figure 1 is an above view of the cot.

The cot fabric 1 is standard cut length and width of existing cots with sleeves down the length and width of the cot to hold the side-rails 4 and the telescoping ski poles 3. There are four side-rails 4 for the cot, each approximately 1/2 the length of the cot. The side-rails 4 will be made to telescope in order to facilitate easier packing or adjust to the use as a main stay of internal frame packs. At each end of the cot are the telescoping ski poles 3. These telescoping ski poles 3, (referred to as trekking poles hereafter) are on the market today and

Deleted: DESCRIPTION: The following descriptions refer to drawing pages 1 through 5. Each page has two drawings referenced as A and B. A and B refer to different angles of the same subject matter. Existing products are not detailed here, only the detail of the invention as it relates to those existing products.¶
Drawing page 1 is an overall look at the cot when it is assembled and the position of all of the related material necessary to have the cot assembled. Figure 1a is an above view of the cot. The cot fabric is standard cut length and width of existing cots with sleeves down the length of the cot to hold the side rails. There are four side rails for the cot, each approximately 1/2 the length of the cot. The side rails will be made to telescope in order to facilitate easier packing or adjust to the use as a main stay of internal frame packs. At each end of each side rail is a lock button and lock similar to that used on umbrellas. This lock secures the side rail to each of the six legs of the cot. At each end of the cot are the trekking poles. These trekking poles are on the market today and have a telescoping feature that would allow them to be used as the end stays of the cot. By reducing the trekking pole to the proper length, inserting them into the end legs and then tensioning the trekking pole, the proper fit could be found. The center stay is made from the ice ax. If the ice ax is not used as a center stay, the ice ax extender will be used as the center stay. The ice ax extender will come in a standard length so it functions as a center stay. The user can then cut down the extender to the proper length if they chose to use the ice ax as a center stay. The position of the ice ax on the leg will be lower down so as not to interrupt the sleeping surface of the cot as shown in figure 1b. In addition, an incline strap will be sewn into the cot in order for the user to raise the cot into a camp chair position for uses other than sleep. The center leg will have a swivel screw in order for this to occur. The detail of the legs that receive the ice ax, trekking poles and side rails are detailed in drawing pages 2 through 5.¶
Drawing page 2 refers to the end

Formatted: Position: Horizontal: Center, Relative to: Margin

5 have a telescoping feature that would allow them to be used as the end stays of the cot. By reducing the trekking pole 3 to the proper length, inserting them into the end legs and then tensioning the trekking pole 3 the proper fit could be found. The center stay is made from the ice ax 2. The position of the ice ax 2 on the center legs will be lower down so as not to interrupt the sleeping surface of the cot as shown in figure 2 by the position of the ax head 14 in relation to the cot. In addition, an incline strap 9 will be sewn into the cot in order for the user to raise the cot into a camp chair position for uses other than sleep. The center leg will have a free floating bolt 30 in order for this to occur. The detail of the legs that receive the ice ax 2, trekking poles 3 and side-rails 4 are detailed in figures 3 through 10.

15 Figures 3 and 4 refer to the pole tip legs 5 that receive the trekking pole tip 10. There is a side view, figure 3 which shows approximate location of the pole tip receiver hole 15 on the pole tip legs. There will be two pole tip legs 5, one for each trekking pole 3. Figure 3 shows how the side-rail 4 is received by the pole tip leg 5 and where the side-rail lock 25 and side-rail lock button 26 are located. Also noted in figure 3 is the rubber boot 28 added to the end of each leg in order to reduce damage to the cot leg and the tent floor of the user. Figure 4 is the same leg as figure 3 only rotated 90 degrees to show how the pole tip 10 is received into the pole tip leg 5. The pole basket 17 will stop the advance of the trekking pole 3 through the leg beyond the pole tip 10. There is no locking mechanism for the pole tip 10 because the trekking pole 3 will be tensioned after insertion into the legs by its existing telescoping feature.

25 Figure 5 refers to the pole handle legs 6 that receive the pole handle 11 end of the trekking pole 3 and its location in regards to the side-rail receiver hole 16, side-rail 4 and shows the side-rail lock 25 and side-rail lock button 26 location. There will be two of these legs, one for each trekking pole 3. Figure 6 is the same as figure 5 only rotated 90 degrees to

- Deleted: 2b, that
- Deleted: hole
- Deleted: end
- Deleted: receiver
- Deleted: . One
- Deleted: . 2a
- Deleted:
- Deleted: how
- Deleted:
- Deleted: is situated.
- Deleted: 2a
- Deleted: This rubber boot will also reduce slippage on slippery surfaces.
- Deleted: 2b
- Deleted: 2a
- Deleted: trekking
- Deleted: receiving
- Deleted: . The tapered design of the pole
- Deleted: of the pole
- Deleted:
- Deleted: Drawing page 3
- Deleted: receiver
- Deleted: other
- Deleted: or the "trekking pole handle" receiver leg. Again as in drawing 2a, the side rail receiver hole is shown as is the side
- Deleted: and associated locking mechanism. Figure 3a
- Deleted: how the pole handle receiver cup is in position to the rest of the leg components. In figure 3b which
- Deleted: 3a except turned
- Deleted: . The
- Formatted: Position: Horizontal: Center, Relative to: Margin

5 show how the pole handle 11 is received into the pole handle leg 6 and its location in regard to the side rail receiver hole 16.

Figures 7 refer to the ax point leg 7 of the cot. There will be one type of this center leg. Figure 7 refers to the ax point leg 7 that receives the ax point 12. In figure 7, the location of the ax point receiver hole 20 is below the side-rail receiver hole 16. This is needed because the ice ax 2, if positioned above the side-rail 4, would interfere with the sleeping surface of the cot. In addition, the upper portion of the center legs is reserved for the swivel motion of the cot incline feature. The figure 7 shows the dotted lines to suggest the various positions of the side-rail 4 as it is adjusted with the incline strap 9. In addition, figure 7 shows a free floating bolt 30 that attaches to each end of the side rail center receiver hole 19 that allow for incline adjustment of the cot. The side-rail lock button 26 and lock 25 are again shown. Figure 8 is the same as figure 7 except turned 90 degrees to show how the ax point 12 is received in relation to the other components of the ax point leg 7. The nature of an ax point 12 which tapers out to the ax shaft 29, will allow the ax point leg to not require a locking mechanism.

20 Figure 9 refers to the details of the ax head leg 8, which receives the ax shaft 29. There is only one of these type legs. The ax receiver hole 23 shows the approximate size of the hole and the ax screw 24, which would clamp down onto the ax shaft 29 after it has been properly tensioned onto the cot. Various side-rail positions 21 are also indicated by the dotted lines. Figure 10 is the same as figure 9 except turned 90 degrees to show the side-rail center receiver hole 19 and the side-rail spacing 22 in relative position to the ax shaft 29 and to the ax head leg 8.

Deleted: receiver cup shows

Deleted: required concavity of the handle receiver leg. This is required so as the user tensions the trekking pole and uses the cot, the pole will not slip out of position. Again, there is not a locking mechanism for the trekking pole because the tensi ... [1]

Deleted: design of each leg w ... [2]

Deleted: Drawing pages 4 and 5

Deleted: center legs

Deleted: of each

Deleted: One

Deleted: point of the ice ax an ... [3]

Deleted: . Drawing page 4 ref ... [4]

Deleted: of the ice ax.

Deleted: 4a

Deleted: ice

Deleted:

Deleted:

Deleted: leg

Deleted: 4a

Deleted: rail

Deleted: . The center of the s ... [5]

Deleted: 4b

Deleted: 4a

Deleted: ice

Deleted: ice

Deleted: ice

Deleted: this

Deleted: Drawing page 5

Deleted: other center

Deleted: shaft and head positi ... [6]

Deleted: as noted again in 5a ... [7]

Deleted: hole

Deleted: required

Deleted: locking

Deleted: ice

Deleted: 5b

Deleted: 5a

Deleted: receptor

Deleted: relating

Deleted: of the ice ax

Deleted: center

Formatted ... [8]

5

Figure 11 refer to the ice ax extender 27. Ice axes come in various lengths depending

Deleted: Special note: Refer to drawing page 6.

Deleted: "

Deleted: point

Deleted: ". This extender

Deleted: There will be a securing screw to hold the extender in place on the ice ax. The extender will come in a standard length which after being sized by its owner, will be cut down in order to save weight. This

on its intended use and the height of its user. Therefore, it may be required to make an ice ax

extender 27. This ice ax extender 27 would fit onto the point end of the ice ax 2, extending its

length. The ice ax extender 27 will be wider at the top in order to fit over an ice ax 2. This

wider portion is called an extender sleeve 31. It then narrows to an extender shaft 32 which

10 resembles the standard size of an ax shaft 29 with an extender point 33 on the end which

resembles an ice ax point 12. The extender sleeve 31 is the area where the user will size the

ice ax 2 to the ice ax extender 27 and the cot and make the appropriate cut to fit on the ice ax

2. There are securing screw holes 34 on the extender sleeve 31 to hold the ice ax extender 27

in place on the ice ax 2. The ice ax extender 27 will come in a standard length which after

15 being sized by its owner, will be cut down in order to save weight. This ice ax extender 27 will

come in a standard length that will serve as the center stay of the cot if the ice ax 2 is not going

to be used as a center stay by the user.

Formatted: Position: Horizontal: Center, Relative to: Margin

5

Summary List of Elements

Deleted: OPERATIONS:

Formatted: Underline

Formatted: Centered, Level 1

Needed for operations are the following:

1. Six ft. by 2 1/2 ft. nylon cot fabric 1 with incline strap 9.
2. Two pole tip receiver legs 5.
3. Two pole handle receiver legs 6.
4. One ax point receiver leg 7.
5. One ax head receiver leg 8.
6. Four telescoping side-rails 4. (Adapted from internal frame backpack stays).
7. Ice ax 2.
8. Ice ax extender 27. (center stay)
9. Two telescoping ski poles 3 (trekking poles).

Deleted: point

Deleted: ice

Deleted: ice

Deleted: shaft

10

15

Detailed list of Elements

1. Cot cloth
2. Ice ax
3. Telescoping ski pole(trekking pole)
4. Side-rails
5. Pole tip legs
6. Pole handle legs
7. Ax point legs
8. Ax head legs
9. Incline strap
10. Pole tip

Formatted: Numbered + Level: 1 + Numbering Style: 1, 2, 3, ... + Start at: 1 + Alignment: Left + Aligned at: 0.25" + Tab after: 0.5" + Indent at: 0.5"

Deleted: <#>Ice ax extender. (center stay)\f
Two telescoping

Deleted: s.

Deleted: The user will lay the cot fabric on the ground insert extended siderails in sleeves. Insert siderails into all six

Deleted: and lock into place. Insert

Deleted: of trekking pole into leg and size so handle fits into appropriate leg. Extend pole until tensioned and tighten down telescoping screws of pole. Repeat for other end of cot. Insert ice ax shaft through ice ax shaft receiver leg hole. Inset

Formatted: Position: Horizontal: Center, Relative to: Margin

20

25

5

11. Pole handle

12. Ax point

14. Ax head

15. Pole tip receiving hole

16. Side-rail receiver hole

17. Pole basket

18. Pole handle receiver

19. Side-rail center receiver hole

20. Ax point receiver hole

21. Various side-rail positions

22. Side-rail spacing

23. Ax shaft receiver hole

24. Ax screw

25. Side-rail lock

26. Side-rail lock button

27. Ice ax extender

28. Rubber boot

29. Ax shaft

30. Free floating bolt

31. Extender sleeve

32. Extender shaft

33. Extender point

34. Extender securing holes

Deleted: of ice ax into ice ax point leg hole. If needed the ice ax extender can be added at this point. Tension ice ax so cot becomes tight. Tighten ice leg

Deleted: on ice ax

Deleted: . Cot

Formatted: Position: Horizontal: Center, Relative to: Margin

Abstract of the Disclosure

A backpacker/mountaineers cot that is lightweight enough to be carried in the backcountry and that is assembled using a minimal of structural cot components in conjunction with various commonly used mountaineer's tools. It allows the elimination of the piece of foam or the inflatable sleeping pad that mountaineers generally backpack. Instead, the mountaineer incorporates his trekking poles, ice ax and internal frame backpack stays with the cot's structural components to form a lightweight, strong or the appropriate assembly of the cot.

Deleted: ready for use.¶

----- Page Break -----

¶
SUMMARY:¶

The backpackers/mountaineers cot will be

Formatted: Indent: First line: 0.5"

Deleted: great addition to anyone's backcountry experience. With the relative little difference

Deleted: weight to be carried, the backpacker could greatly increase his/her comfort regardless of ground conditions. By using tools already being used for other purposes the user is reducing overall weight while greatly increasing comfort. The parallels of equipment is as follows: The user has trekking poles, ice ax, sleeping pad, sleeping pad camp chair and internal frame backpack. The cot user will exchange the sleeping pad and chair for the cot fabric and six cot legs. By adapting the internal frame backpacking stays into the siderails of the cot and using the trekking poles and ice ax as the end and center stays of the cot the user will have the ultimate in efficiency and comfort in the backcountry environment

Deleted: ----- Page Break -----

¶

ABSTRACT:¶

A backpacker/mountaineers cot lightweight enough to be carried in the backcountry using tools already employed for other purposes and carried by the user. The user is exchanging the use of foam or inflating sleeping pad and sleeping pad camp chair for a cot fabric and six cot legs. The user then incorporates the trekking poles, ice ax and internal frame backpack stays for the appropriate assembly of the cot.¶

Formatted: Position: Horizontal:
Center, Relative to: Margin

5

CLAIM (S):

I claim:

Formatted: Level 1

Deleted: I Claim:¶
A lightweight
backpackers/mountaineers cot
comprising

1. A mountaineer's cot comprised of the following elements:

at least two cot legs; and

a cot cloth;

wherein said elements allow for the interconnection of tools already carried by

the backpacker and mountaineer and used for other purposes to form a

lightweight cot.

Formatted: Level 1, Indent: Left:
0.25", First line: 0.25"

Deleted: nylon fabric with siderail
sleeves six cot legs; the two center
legs being constructed to receive an
ice ax as the center stay and four end
legs constructed to receive the
trekking poles as end stays of the cot.
The siderails telescoping in nature
are adapted from the internal frame
backpack stays.

2. The mountaineer's cot of claim 1 wherein the number of legs is six.

3. The mountaineer's cot of claim 2 wherein said cot cloth has the dimensions of 2

feet by 6 feet.

4. A lightweight mountaineer's cot comprised of :

at least 4 legs;

a cot cloth;

a cot frame adapted for field assembly from a combination of mountaineering

tools.

5. The mountaineer's cot of claim 4 wherein said mountaineering tools are selected

from the set of mountaineering tools consisting of an ice ax, telescoping ski poles

and internal frame pack mainstays.

Deleted: The siderails adjusted in
length after removal from the internal
frame backpack slid into the
sidesleeves of the cot fabric. The
siderails then are locked into the cot
legs at the designated siderail
receiver holes. The trekking poles are
then adjusted from the trekking
position length to the length that is
appropriate for the end stays of the
cot. The trekking poles are then fitted
to the point of cot function. The ice ax
is then fitted to the center legs and
tightened to the proper tension and
locked into place with the center leg
ice ax shaft tightening screw. The six
legs are specific for the reception of
the particular end and center stay.
There are two end legs that are
designed to receive the point of the
trekking pole and two legs designed
to receive the handle of the trekking
poles. There is one center leg
designed to receive the point of the
ice ax and one center leg designed to
receive the shaft of the ice ax. The
center legs are also designed with a
swivel bolt attached to the siderail
receiver that allows the inclination of
the cot to be adjusted by the user
from lying to sitting position. In
addition, there is an ice ax extender
the allows the user to extend the
length of their ice ax to the
appropriate size in order to properly fit
the cot for use. The ice ax extender
has a locking screw that will lock the
extender to the ice ax for cot use.¶

Formatted: Position: Horizontal:
Center, Relative to: Margin

Formatted: Position: Horizontal:
Center, Relative to: Margin

Page 7: [1] Deleted hicks 5/4/2006 5:04:00 PM

required concavity of the handle receiver leg. This is required so as the user tensions the trekking pole and uses the cot, the pole will not slip out of position. Again, there is not a locking mechanism for the trekking pole because the tension of the telescoping pole and the

Page 7: [2] Deleted hicks 5/4/2006 5:04:00 PM

design of each leg will lock the pole in place

Page 7: [3] Deleted hicks 5/4/2006 5:04:00 PM

point of the ice ax and one leg that receive the shaft of the ice

Page 7: [4] Deleted hicks 5/4/2006 5:04:00 PM

. Drawing page 4 refers to the center leg that receives the

Page 7: [5] Deleted hicks 5/4/2006 5:04:00 PM

. The center of the side rail receiver hole will have a swivel screw that is free floating in the up and down motion.

Page 7: [6] Deleted hicks 5/4/2006 5:04:00 PM

shaft and head position of the ice

Page 7: [7] Deleted hicks 5/4/2006 5:04:00 PM

as noted again in 5a, the side rail receiver swivel screw and various possible incline positions. The

Page 1: [8] Formatted hicks 5/4/2006 5:04:00 PM

Position: Horizontal: Center, Relative to: Margin